

SELECT MODEL

1 Series	CZ 300DGC	
2 Type	G Gauge GS Gauge + Switch	S Switch
3 Body material	A Aluminum B Brass	S SS-316 M Monel
4 Dial size	2.5 2.5" (63mm) 3.5 3.5" (80 mm) 4.0 4.0" (100mm)	4.5 4.5" (115 mm) 6.0 6.0" (150 mm)
5 Connection	4N 1/4" NPT (F) (Std.) ZZ Special connection sizes using adaptor	4B 1/4" BSP (F)
6 Porting	1 In-line (Std.) 2 Rear / Back 3 Bottom 4 Bottom & vent	5 In-line & vent 6 In-line & bottom 7 Bottom vent & in-line 8 In-line & back
7 Case	S4 SS 304 (Std.) F4 SS 304 flange EP Engineering polymer (available in 2.5", 4.5", 6.0" only) BF Bayonet (available in 4.0" safety glass only)	S6 SS 316
8 Window	F Glass (Std.) T Toughened glass	A Acrylic L Safety glass
9 Seals/Diaphragm	B Buna-N (Std.) V Viton	E EPDM
10 Switch	Select option & specifications	

Advantages :
Instrument automatically resets after line surges and cold start.
This eliminates balancing of differential pressure instrument after such events.

Notes

- Switch option not available with inline vent / bottom vent porting.
- Top vent not available with switch option.
- For SS 316 case, please contact factory (MOQ applies).
- Liquid filling + Follower pointer available.
- For Switch adjustment range and other specific details regarding the switch, please contact factory.
- Mounting bracket: Aluminum (Standard) ; SS (Optional)

5	One SPDT, with a DIN plug †
6	One SPDT, with a terminal strip
7	Two SPDTs, with two DIN plugs
8	Two SPDTs, with a terminal strip

+

SPDT Specifications (AC/DC max)

1 Standard	2	3
3 VA	5 VA	5 VA
30 V	125 V	175 V
0.3 Amp	0.25 Amp	0.25 Amp
Adjustable	Adjustable	Adjustable

Example: Switch selection 51 is 1 SPDT with DIN plug with switch specifications 3VA, 30V, 0.3Amp
† DIN plug mounted on the top.

11 Range

Standard ranges : (Other ranges & units on request)


Kg/cm²	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
bar	0.075	0.25	-	0.5	0.75	1	-	1.6	2	2.5	3	-	4
mbar	75-	250	-	-	750	-	-	-	-	-	-	-	-
psi	1	-	5	8	-	15	20	25	30	-	40	50	60
kPa	-	25	-	50	75	100	-	160	200	250	300	-	400

12 Options

- 0 None
- A Glycerine*
- B Red follower pointer on acrylic window *
- C Customer Logo
- D Dual scale
- E Colour band
- F Filter mesh in (+) connection
- N NACE
- S Silicone oil*
- I Oxygen service (Contact factory)
- M1 2" horizontal pipe mounting bracket
- M2 Surface mounting bracket
- M3 2" vertical pipe mounting bracket

* Affects accuracy

Ordering code sequence



Contact factory for special execution.